	SPACIFICATIONS	
1	MODEL	MTP/OP-12
2	DENIER RANGE	5000 TO 20000 DENIER
3	FLYER SPEED	2800 RPM MAX
4	TWIST PER MINUT	5600 TWIST MAX.
5	TWIST DIRECTION	S OR Z
6	YARN FLOW	OUTSIDE
7	PAY OFF PACKAGE SIZE	DIA. 350 MM X TRA. 300 MM (MAX.)
8	PAY OFF PACK. CAPACITY	16 KGS (APPROX)
9	PACKAGE IN EACH STRAND	1
10	TPM RANGE	20 TO 150 TPM
11	FINAL PACKAGE SIZE (ANY ONE)	150 X 150 MM 200 X 200 MM 250 X 250 MM 300 X 300 MM
12	SPINDLE	CORELESS PNEUMATIC SPINDLE
13	NO OF LINE	4
14	POWER	17 KW

KEY FEATURES

USER FRIENDLY TOUCH SCREEN DISPLAY
TPM & RPM ADJUSTMENT BY TOUCH SCREEN DISPLAY
WINDING TENSION ADJUSTMENT BY TOUCH SCREEN DISPLAY
PITCH ADUSTMENT SYSTEM
INDIVIDUAL PREDETERMIND LENGTH SET POINT
AUTO STOP AT YARN BRACKAGE
POWER TRANSMISSION BY TIMMING BELTS
AC FREQUENCY DRIVES FOR ALL MOTORS
PRECISION CROSS WINDING FOR FINAL PACKAGE
ELECTRICALY WINDING TENSION ADJUSTMENT